

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: G11B 20/10	A1	(11) International Publication Number: WO 00/68945
		(43) International Publication Date: 16 November 2000 (16.11.00)

(21) International Application Number: PCT/US00/12810

(22) International Filing Date: 10 May 2000 (10.05.00)

(30) Priority Data:
60/133,456 11 May 1999 (11.05.99) US(71) Applicant: MACROVISION CORPORATION [US/US]; 1341
Orleans Drive, Sunnyvale, CA 94089 (US).(72) Inventor: DOWNING, Daniel, D.; P.O. Box 371048, Montara,
CA 94037 (US).(74) Agents: STEWART, Daniel, P. et al.; Skjerven, Morrill,
MacPherson, Franklin & Friel LLP, 25 Metro Drive, Suite
700, San Jose, CA 95110 (US).

(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: SECURE COMPACT DISK AND PLAYER

(57) Abstract

A method for recording data on an optical medium is disclosed. In one embodiment, the method includes receiving a first plurality of frames of data at a Cross Interleave Reed-Solomon Code (CIRC) encoder, encoding the first plurality of frames of data by the CIRC encoder to generate a second plurality of frames of data, generating a set of data to form a Q sub-channel, altering selected data bits in the Q sub-channel to form an encoded Q sub-channel, forming a plurality of control bytes including the encoded Q sub-channel, adding one of the control bytes to each one of the second plurality of frames of data to generate a third plurality of frames of data, encoding selected portions of the third plurality of frames of data by an EFM encoder to generate a plurality of channel frames, and recording the channel frames on the optical medium. This method allows CDs to be recorded that cannot be played by conventional CD players. A corresponding optical disk playback system and method for receiving, decoding and presenting data are also disclosed.



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

SECURE COMPACT DISK AND PLAYER

TECHNICAL FIELD OF THE INVENTION

5 This invention relates to compact disks and compact disk players, specifically to a secure system involving proprietary compact disk formats and associated compliant players to prevent copying and unauthorized use of compact disk program material.

BACKGROUND OF THE INVENTION

10 Compact disks (CDs) are well known; there is a variety of types of compact disks. For instance, CDROMs typically hold computer programs and data. There are also audio compact disks which hold music, etc. and video compact disks for material such as movies. Each type of compact disk has an associated player. There are a variety of compact disk standards.

 Compact disks are a digital storage media, unlike conventional videotape. Therefore
15 copies of such digital material contain all of the information of the original and are a frequent target for pirates (copyright infringers) who make unauthorized copies or otherwise misuse same. There have been developed a number of security systems to prevent unauthorized copying in the compact disk field.

 The present invention is directed to a particular aspect of the security problem of
20 compact disks including video CDs and CDROMs (data CDs). Specifically, there is a need for a compact disk player that only plays proprietary CDs, does not play standard CDs, where the proprietary CDs cannot be copied and the proprietary CDs do not play on standard CD players. Thus this is a "closed" system involving proprietary (in terms of the format) CDs and

associated players. A typical application is for a toy system where there is no need to play generally available CDs but only the toy system's CDs are of interest.

Any such system must be relatively inexpensive to implement (since these are consumer players), and must be robust so as to prevent copying, and not interfere with playing and enjoyment of the CD program material. The cost requirement is especially restrictive since even a few dollars of added cost are problematic in consumer electronics. Therefore, well-known methods such as encryption may be problematic since they may require inclusion in the player of a dedicated decryption integrated circuit. Since the decryption must be performed in real time, software decryption is generally less useful in this context.

SUMMARY OF THE INVENTION

In an otherwise conventional compact disk player and compact disk, an improvement accomplishes the above goals. This improvement has the above effects of, for the proprietary ("compliant") compact disk player, allowing it only to play compliant CDs; the compliant player will not play standard CDs; the proprietary CDs cannot be copied (that is, if copied they cannot be successfully played on either a compliant player or a standard player); and the compliant CDs do not play on a standard CD player. Thus this creates an entirely closed system in terms of the compliant CDs and associated compliant players. Anyone wishing to play a compliant CD must have a compliant player, the use of which is limited to playing compliant CDs. Of course such a system is targeted to particular markets and requires availability of both the compliant players and the compliant CDs.

In accordance with one aspect of the present invention, a method for recording data on an optical medium is disclosed. In one embodiment, the method includes receiving a first plurality of frames of data at a Cross Interleave Reed-Solomon Code (CIRC) encoder,

encoding the first plurality of frames of data by the CIRC encoder to generate a second plurality of frames of data, generating a set of data to form a Q sub-channel, altering selected data bits in the Q sub-channel to form an encoded Q sub-channel, forming a plurality of control bytes including the encoded Q sub-channel, adding one of the control bytes to each one
5 of the second plurality of frames of data to generate a third plurality of frames of data, encoding selected portions of the third plurality of frames of data by an EFM encoder to generate a plurality of channel frames, and recording the channel frames on the optical medium.

In accordance with another aspect of the present invention, a method for receiving,
10 decoding and presenting data is disclosed. In one embodiment, the method includes receiving a plurality of channel frames of data at an EFM decoder, decoding the channel frames using EFM decoding to generate F3 frames, locating Q sub-channel bits in respective control bytes of the F3 frames, selectively inverting the Q sub-channel bits to generate decoded Q sub-channel information, and decoding and presenting the F3 frames using the decoded Q sub-
15 channel information.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and for further features and advantages, reference is now made to the following description taken in conjunction with the accompanying drawings, in which:

5 FIG. 1A shows a first portion of a process for creating a compliant CD in accordance with this invention;

FIG. 1B shows a continuation of the process of FIG. 1A; and

FIG. 2 is a simplified block diagram of an exemplary CD playback system designed to operate in accordance with the present invention.

10

DETAILED DESCRIPTION OF THE INVENTION

The preferred embodiments of the present invention and their advantages are best understood by referring to FIGURES 1A and 1B of the drawings. Like numerals are used for like and corresponding parts of the various drawings.

15 This invention is generally directed to compact disks and players. It is not limited to CDROMs (typically used for computer data), or video CDs. The embodiment described herein is for video CDs but is applicable to other types of CDs with suitable modifications, as apparent to one skilled in the art from this disclosure.

20 The process described herein is in the context of CDROMs and the terminology is in accordance with the ISO/IEC 10149, Second Edition (1995-07-15) specification for CDROMs, which is incorporated herein by reference in its entirety. With suitable modifications this is applicable to video CDs.

FIGs. 1A and 1B together show a process flow for creating a compliant CD in accordance with this invention. Most of FIGs. 1A and 1B is conventional, except for two data

alterations. Hence while the following description is of the entire CD creation (writing) process, it is to be understood that most of this is conventional and disclosed here only for background purposes. The above specification gives further detail of the data structures on a typical CD. Again this is merely illustrative of one CD specification standard.

5 Beginning in the upper left hand portion of FIG. 1A there is the incoming "sector" data 12. The term "sector" refers to this being digital data already partitioned into sectors.

 This incoming data 12 is in various fields. The associated overhead sync field 14, header field 16, and EDC (Error Detection Code) field 22 are created by the CDRom encoder. The incoming data is put in the user data field 18. The small numerals under each field name
10 designate the field length in bytes. The user data is the largest field. The other fields are the overhead fields.

 The sync field 14 is then passed directly to the next step 14'. This is combined with the IF (intermediate field) field 28. The resulting fields including the IF field 28' are shown below the Reed Solomon processing 32. The IF field is eight bytes of zero value. Added at
15 this point, due to the Reed Solomon processing, is the Q field. The P and Q fields are the Forward Error Correction codes. At this point the header, user data, EDC, P and Q fields are
 subject to a scrambler 46 using the scrambling algorithm 46. This results in a 2,352 byte data structure 48.

 Processing continues at B. (Reference character B merely shows the continuation of
20 the process.) In FIG. 1B, next is the F1 mapper 52, which maps the 2,352 byte data structure 48 into 98 F1 frames designated 0 through 97. (These frames are not the same as ordinary video frames.) Each F1 frame 54 has a length of 24 bytes.

 Up to this point, all processing is conventional. At this point, scrambling (inversion) in accordance with this invention is introduced by processing the F1 frame data 54 through

inverter 58. (An alternative to this scrambling is encryption.) Inverter 58 accepts one F1 frame at a time, as shown by the switching process 60 which conventionally interleaves the frames. Each frame is subject to a simple bit-by-bit inversion of all its data including the sector address information. Thus each 1 bit is inverted to 0 and each 0 bit is inverted to 1.

5 Subsequent processing is conventional, including the Cross Interleaved Reed-Solomon Code (CIRC) encoding 62. The CIRC encoder as shown accepts data from the inverter or from an audio input.

10 The CIRC encoder 62 adds 8 bytes of data to each of the 98 F1 frames. This data is spread out over 106 F2 frames, each of 32 bytes. The F2 frame data which includes the CIRC information from the CIRC encoder 62 thus becomes 106 32-byte frames stored in register 68. This is read out by switching process 70 to become 98 33-byte F3 frames 74, which form a section. F3 frames are identical to F2 frames except for the added control byte 82.

15 The information for each frame in the P, Q, R, S, T, U, V and W sub-channels is added as shown to form the control byte 82 of 8 bits. Thus there is a single bit in byte 82 for each sub-channel P through W. These sub-channels are for control purposes. The typical use of the P sub-channel is for an audio player to indicate when the audio starts and stops. The Q sub-channel typically includes the table of contents of the program information in the lead-in area of the disk, and includes index and elapsed time information in the user data area of the disk, as specified in ISO/IEC 10149. The other sub-channels typically are not used.

20 In accordance with this invention, there is an additional scrambling step in which at least the sector address information in the Q sub-channel table of contents is scrambled or otherwise altered by a Q sub-channel encoder 80. Two examples of such alteration of the Q sub-channel are described herein. However, it will be understood that other methods of encoding the Q sub-channel may be used.

In the first example, the entire Q sub-channel, or selected portions thereof, are subject to an inversion. P, Q, R, S, T, U, V, W sub-channel processing is typically performed off-line and, in accordance with this invention, also involves subjecting, in the Q sub-channel, at least the sector address information to an inversion by Q sub-channel encoder 80. Thus at least the
5 sector address information in the Q sub-channel is subject to this inversion, on a bit-by-bit basis. The resulting control byte 82 is then appended to each of the F3 frames.

In the second example of Q sub-channel encoding, a portion of the Q sub-channel is scrambled using an exclusive-OR function in Q sub-channel encoder 80. The Q sub-channel of a 98-frame section typically comprises 96 bits, since the first two control bytes of a section
10 are occupied by the S0 and S1 bytes. The Q sub-channel of a section typically comprises a control field (four bits), a q-Mode field (four bits), a q-Data field (72 bits) and a cyclical redundancy check (CRC) field (16 bits). In accordance with the present invention, the first 80 bits of the Q sub-channel may be scrambled using the XOR function described below, while the last 16 bits which make up the CRC field are computed in the usual fashion.

15 The first 80 bits of the Q sub-channel may be treated as 10 eight-bit bytes. These 10 bytes may be XORed on a byte-by-byte basis with 10 eight-bit encoding bytes. The encoding bytes may be selected arbitrarily. An exemplary set of 10 encoding bytes is set forth in Table

A.

TABLE A

	Byte	Value
	0	01110001
	1	10001110
5	2	00110011
	3	11001100
	4	10101010
	5	01010101
	6	11110000
10	7	00001111
	8	11111111
	9	00000000

15 It will be understood that this second exemplary method of encoding the Q sub-channel simply provides selective inversion of Q sub-channel bits. Wherever a "one" occurs in an encoding byte, the corresponding bit of the Q sub-channel is inverted, while a "zero" in the encoding byte means that the corresponding bit of the Q sub-channel is left unchanged. This is in contrast to the first exemplary encoding method described above, in which all bits of at least
20 a portion of the Q sub-channel are inverted.

 This Q sub-channel scrambling, by itself novel and useful, may eliminate the need for the other inverter (inverter 58 in Fig. 1B). Scrambling the Q sub-channel address information may provide some protection, but scrambling most of the information provides more protection. As previously described, the format for the data stored in the Q sub-channel varies
25 depending upon its location on the CD. The general format is data followed by the CRC. In ~~accordance with this invention~~, the data portion is altered prior to the calculation of the CRC. There is one portion of this data which in some instances may not be altered.

 The 98 F3 frames are eventually written to the CD as a series of channel frames, where the first channel frame has the control byte forced to be the conventional S0 sync symbol and

the second channel frame has the control byte forced to be the conventional S1 sync symbol. S0 and S1 sync symbols have no relationship to the "Sync Header" block 90 in Fig. 1B. If one envisions how an optical pickup head would sense data on a CD, one imagines it as seeing a series of bits being picked up from the disk (i.e., in serial fashion), in order to reconstruct the 98 F3 frames. One needs some way of identifying frame F3-0 or F3-1. This is done by looking for either the S0 or S1 symbols. Therefore one cannot alter the S0 or S1 symbols in systems that use a standard IC (integrated circuit) that only detects the standard (i.e., non inverted) S0 or S1 symbol. Further, the CRC is not altered either because in systems that use a standard IC with CRC, the verification circuitry would (falsely) determine that the CRC is wrong.

In systems that use standard ICs one must be careful about which parts of the data are inverted so that the S0 and S1 symbols can be successfully detected (in those channel frames that have them) and that the CRC can be recovered correctly.

The following processing in Fig. 1B is conventional, and includes EFM encoding 86. This requires encoding such that between two 1's there a minimum of two 0's or a maximum of ten 0's. This EFM encoding is performed for signal processing purposes. At this point, additionally the merging bits 88 (three per EFM symbol), the sync header 90 and the merging bits (for the sync header) 92 are added, resulting in the channel frame 96. This is then subject to the non-return to zero inverted (NRZI) encoding 98. The NRZI encoded information is then written onto a master disk 100. This master disk is then used conventionally to produce "stampers" which press out the plastic disks which are commercially distributed.

Hence FIGs. 1A and 1B show the CD encoding (writing) process. For video CDs, a similar process is used except that there is no IF field, Reed Solomon processing, or P and Q fields.

The compliant player which is to read the resulting CDs, while largely conventional, includes two suitable logic functions respectively complementary to inverter 58 and Q sub-channel encoder 80. These two functional blocks in the player respectively (1) re-invert data in the data stream and (2) decode the Q sub-channel in accordance with the encoding method used. Hence the compliant player is conventional except for these two additional logic functions. The inverters need not be hardware devices but may be software functions, given adequate processing speed. The same of course is true for the inverter 58 and Q sub-channel encoder 80 in FIG. 1B; they may be hardware logic or software logic functions.

In another embodiment, there may be only one inversion process e.g., in the Q sub-channel or in the data stream rather than two as shown in FIG. 1B. However, it is preferred to have two inversions or alterations as shown in FIG. 1B. This ensures that standard players are unable to play a compliant CD-ROM. In the absence of one of the inversion processes, some conventional (non-compliant) players may be able to play such a compliant disk, which is considered undesirable.

Also, in another embodiment there is no inversion but instead the only change is in the sector address information in the Q sub-channel. In this embodiment, rather than being in the Q sub-channel, the sector address information is instead put in one of the unused sub-channels such as R, S, T, etc. In this case there is no inversion or scrambling. Again the compliant player must be complementary to read the sector address from the correct sub-channel in which this information is now located.

The simple inversion scrambling of FIG. 1B is of course not limiting. Other types of more sophisticated scrambling and/or encryption may be used. However even the simplest type of scrambling is effective in this context.

Referring to FIGURE 2, a simplified block diagram of an example of a CD playback system 102 is shown. Playback system 102 includes a CD reading and NRZI decoding system 104, which may include laser optical elements for reading information from CD 100 and a conventional NRZI decoder to extract data bits from the resulting signal. The data generated by CD reading and NRZI decoding system 104 includes data in the form of channel frames.

A conventional EFM decoding system 106 converts the fourteen-Channel bit bytes of the channel frames to eight-bit bytes, thereby generating a series of F3 frames. EFM decoding system 106 discards the merging bits and sync header information from the data stream.

A control block 108 extracts the control bytes from the F3 frames to generate F2 frames. The Q sub-channel data from the control bytes is provided to a Q sub-channel decoder 110, which performs a decoding function corresponding to the encoding function performed by Q sub-channel encoder 80 shown in FIGURE 1B. For example, when Q sub-channel encoder 80 performs an XOR function using a set of encoding bytes as previously described, Q sub-channel decoder 110 may decode the Q sub-channel by performing an XOR function on the encoded Q sub-channel using the same set of encoding bytes, thereby restoring the original Q sub-channel information. The restored or decoded Q sub-channel may then be used by other parts of playback system 102 (not shown) in a conventional manner to assist in the decoding and presentation of the data from CD 100.

The F2 frames generated by control block 108 are provided to a CIRC decoder 112, which operates in a conventional manner to decode the F2 frames to generate either audio data or F1 frames. The resulting F1 frames may be inverted by an inverter 114 if an inverter 58 (shown in FIGURE 1B) is used in the CD recording process.

An F1 mapper 116 receives the inverted F1 frames and uses a conventional mapping function to obtain scrambled sector data, which is then descrambled by descrambler 118 to

restore the original sector data. This sector data is then provided to a presentation system 120, which may include digital to analog converters, speakers, a display screen, or other conventional equipment to present the sector data from CD 100 to a user. Audio data decoded by CIRC decoder 112 may be provided directly to presentation system 120 for presentation to
5 the user.

By performing the inverse of the data encoding functions illustrated in FIGURES 1A and 1B, CD playback system 102 is able to play back a CD 100 recorded using the methods described above, which may not be played back by conventional CD playback systems.

It will be appreciated that the present method and apparatus are not limited to video;
10 also computer data and audio program material on CDs may be protected as disclosed herein. In addition to the above-described scrambling, one may use encryption or other ways of altering, in a systematic or reversible way, the Q sub-channel information.

Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions, and alterations can be made therein
15 without departing from the spirit and scope of the invention as defined by the appended claims.

CLAIMS

I claim:

1. A method for receiving, decoding and presenting data, comprising:

receiving a plurality of channel frames of data at an EFM decoder;

5 decoding the channel frames using EFM decoding to generate F3 frames;

locating Q sub-channel bits in respective control bytes of the F3 frames;

selectively inverting the Q sub-channel bits to generate decoded Q sub-channel
information; and

decoding and presenting the F3 frames using the decoded Q sub-channel information.

10

2. The method of claim 1, wherein decoding and presenting the F3 frames
comprises:

removing a control byte from each F3 frame to generate an F2 frame;

receiving the F2 frame at a Cross Interleave Reed-Solomon Code (CIRC) decoder; and

15 decoding the F2 frame by the CIRC decoder.

~~3. The method of claim 2, wherein decoding and presenting the F3 frames further~~
comprises:

descrambling the output of the CIRC decoder to generate a data stream; and

20 presenting the data stream in a perceptible form to a user.

4. The method of claim 3, wherein decoding and presenting the F3 frames further
comprises inverting the output of the CIRC decoder prior to descrambling the output of the
CIRC decoder.

5. An optical disk playback system comprising:

a data reading system operable to read a plurality of channel frames from an optical disk;

5 an EFM decoder operable to decode the channel frames to generate F3 frames;

a Q sub-channel decoder operable to locate Q sub-channel bits in respective control bytes of the F3 frames and to selectively invert the Q sub-channel bits to generate decoded Q sub-channel information; and

10 a signal decoding and presentation system operable to receive the F3 frames, and operable to decode the F3 frames to generate a data stream using the decoded Q sub-channel information, and operable to present the data stream in a perceptible form to a user.

6. The optical disk playback system of claim 5, wherein the signal decoding and presentation system comprises:

15 a control block operable to remove a control byte from each F3 frame to generate an F2 frame;

a Cross Interleave Reed-Solomon Code (CIRC) decoder operable to receiving and decode the F2 frame.

20 7. The optical disk playback system of claim 6, wherein the signal decoding and presentation system further comprises:

a descrambling system operable to descramble the output of the CIRC decoder to generate a data stream; and

a presentation system operable to present the data stream in a perceptible form to a user.

8. The optical disk playback system of claim 7, wherein the signal decoding and presentation system further comprises an inverter operable to invert the output of the CIRC decoder prior to the descrambling of the output of the CIRC decoder by the descrambling system.

9. A method for recording data on an optical medium, comprising:
10 receiving a first plurality of frames of data at a Cross Interleave Reed-Solomon Code (CIRC) encoder;

encoding the first plurality of frames of data by the CIRC encoder to generate a second plurality of frames of data;

generating a set of data to form a Q sub-channel;

15 altering selected data bits in the Q sub-channel to form an encoded Q sub-channel;

forming a plurality of control bytes including the encoded Q sub-channel;

adding one of the control bytes to each one of the second plurality of frames of data to generate a third plurality of frames of data;

encoding selected portions of the third plurality of frames of data by an EFM encoder

20 to generate a plurality of channel frames: and

recording the channel frames on the optical medium.

10. The method of claim 9, wherein altering the selected data bits in the Q sub-channel to form the encoded Q sub-channel comprises:

reading a plurality of stored encoding bits; and

performing an exclusive-OR operation between the selected data bits in the Q-sub-channel and corresponding ones of the encoding bits.

5 11. The method of claim 10, further comprising:

scrambling a sector of data to generate a scrambled sector; and

rearranging the scrambled sector to generate the first plurality of frames of data.

12. The method of claim 11, further comprising inverting the first plurality of
10 frames of data prior to receiving the first plurality of frames of data at the CIRC encoder.

13. The method of claim 9, wherein altering the selected data bits in the Q sub-channel to form the encoded Q sub-channel comprises relocating the selected data bits in the Q sub-channel to respective alternative sub-channel locations of the control bytes.

15

14. An optical disk playback system comprising:

a data reading system operable to read a plurality of channel frames from an optical disk;

an EFM decoder operable to decode the channel frames to generate F3 frames;

20 a Q sub-channel decoder operable to locate Q sub-channel bits in alternative sub-channel locations in control bytes of the F3 frames to generate Q sub-channel information; and

a signal decoding and presentation system operable to receive the F3 frames, and operable to decode the F3 frames to generate a data stream using the Q sub-channel information, and operable to present the data stream in a perceptible form to a user.

15. A method for recording data on an optical medium, comprising:

receiving the data at an encoding system

assigning the data to a plurality of data sets by the encoding system:

5 generating address information for each data set:

encoding the address information for each data set without otherwise altering the data.

set;

joining each data set with its respective encoded address information to form an
addressed data set;

10 recording the addressed data sets on the optical medium.

16. The method of claim 15, further comprising encoding each addressed data set
prior to recording the addressed data set on the optical medium.

15 17. The method of claim 16, wherein encoding each addressed data set comprises
performing EFM encoding on the data set.

18. The method of claim 17, wherein encoding each addressed data set further
comprises performing NRZI encoding on the data set.

20

19. The method of claim 15, wherein the address information comprises a Q sub-
channel.






FIG. 1A

6



**FIG. 2**

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 00/12810

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B20/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 10. 31 October 1996 (1996-10-31) & JP 08 153331 A (APPLICS:KK), 11 June 1996 (1996-06-11)	14,15
A	abstract	1-12
A	WO 98 52114 A (IMATION CORP) 19 November 1998 (1998-11-19) page 7, line 15 -page 10, line 23	1-12
A	EP 0 418 964 A (PHILIPS NV) 27 March 1991 (1991-03-27) column 4, line 34 -column 6, line 4; figures 1-4	1-12
	-/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "Z" document member of the same patent family

Date of the actual completion of the international search

16 October 2000

Date of mailing of the international search report

23/10/2000

Name and mailing address of the ISA

European Patent Office, P.O. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel: (+31-70) 340-2040, Tx: 31 651 400 nl,
Fax: (+31-70) 340-3016

Authorized officer

Brunet, L

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 00/12310

C. (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	ECMA STANDARDIZING INFORMATION AND COMMUNICATION SYSTEMS: "Standard ECMA - 130 : Data interchange on read-only 120 mm optical disks (CD-ROM)" STANDARD ECMA-130. XP002143627 Geneva, Switzerland paragraph '014.1 - paragraph '19.1! paragraph '22.0! - paragraph '22.3.6! ---	1-19
A	WO 98 03973 A (PHILIPS ELECTRONICS NV :PHILIPS NORDEN AB (SE)) 29 January 1998 (1998-01-29) claims 1.2; figures 1-3,7 ---	14-19
A	WO 98 52194 A (IMATION CORP) 19 November 1998 (1998-11-19) page 6, line 14 -page 8, line 2; claim 1 ---	14-18
A	EP 0 783 167 A (SONY CORP) 9 July 1997 (1997-07-09) figures 6,7 -----	1,5,9, 14,15

INTERNATIONAL SEARCH REPORT

Information on patent family members

Internal Application No

PCT/US 00/12310

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 08153331 A	11-06-1996	NONE	
WO 9852114 A	19-11-1998	AU 7362198 A	08-12-1998
EP 0418964 A	27-03-1991	AT 118288 T	15-02-1995
		AU 657465 B	16-03-1995
		AU 6266690 A	11-04-1991
		BR 9004656 A	10-09-1991
		CA 2025644 A	22-03-1991
		CN 1050457 A,B	03-04-1991
		CZ 9004536 A	14-07-1999
		DE 69016725 D	23-03-1995
		DE 69016725 T	07-09-1995
		DK 418964 T	10-07-1995
		ES 2070267 T	01-06-1995
		HK 75696 A	10-05-1996
		HU 54822 A,B	28-03-1991
		JP 3108162 A	08-05-1991
		KR 231670 B	15-11-1999
		SU 1836721 A	23-08-1993
		US 5428598 A	27-06-1995
		US 5453968 A	26-09-1995
WO 9803973 A	29-01-1998	CA 2232818 A	29-01-1998
		EP 0852053 A	08-07-1998
		JP 11514126 T	30-11-1999
		US 5930209 A	27-07-1999
WO 9852194 A	19-11-1998	AU 7472998 A	08-12-1998
EP 0783167 A	09-07-1997	JP 9161375 A	20-06-1997
		US 5825731 A	20-10-1998

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 November 2000 (16.11.2000)


PCT

(10) International Publication Number
WO 00/68945 A1


- (51) International Patent Classification: G11B 20/10 (72) Inventor: DOWNING, Daniel, D.; P. O. Box 371048, Montara, CA 94037 (US).
- (21) International Application Number: PCT/US00/12810 (74) Agents: STEWART, Daniel, P. et al.; Skjerven Morrill MacPherson LLP, Suite 700, 25 Metro Drive, San Jose, CA 95110 (US).
- (22) International Filing Date: 10 May 2000 (10.05.2000)
- (25) Filing Language: English (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (26) Publication Language: English (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (US)
- (30) Priority Data: 60/133,456 11 May 1999 (11.05.1999) US
- (71) Applicant: MACROVISION CORPORATION
[US/US]: 1341 Orleans Drive, Sunnyvale, CA 94089 (US).

[Continued on next page]

(54) Title: SECURE COMPACT DISK AND PLAYER



(57) Abstract: A method for recording data on an optical medium is disclosed. In one embodiment, the method includes receiving a first plurality of frames of data at a Cross Interleave Reed-Solomon Code (CIRC) encoder, encoding the first plurality of frames of data by the CIRC encoder to generate a second plurality of frames of data, generating a set of data to form a Q sub-channel, altering selected data bits in the Q sub-channel to form an encoded Q sub-channel, forming a plurality of control bytes including the encoded Q sub-channel, adding one of the control bytes to each one of the second plurality of frames of data to generate a third plurality of frames of data, encoding selected portions of the third plurality of frames of data by an EFM encoder to generate a plurality of channel frames, and recording the channel frames on the optical medium. This method allows CDs to be recorded that cannot be played by conventional CD players. A corresponding optical disk playback system and method for receiving, decoding and presenting data are also disclosed.



(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent
(AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LI,
MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GW, ML, MR, NE, SN, TD, TG).

(15) Information about Correction:

see PCT Gazette No. 08/2002 of 21 February 2002, Section
II

Published:

with international search report

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(48) Date of publication of this corrected version:

21 February 2002

SECURE COMPACT DISK AND PLAYER

TECHNICAL FIELD OF THE INVENTION

5 This invention relates to compact disks and compact disk players, specifically to a secure system involving proprietary compact disk formats and associated compliant players to prevent copying and unauthorized use of compact disk program material.

BACKGROUND OF THE INVENTION

10 Compact disks (CDs) are well known; there is a variety of types of compact disks. For instance, CDRoms typically hold computer programs and data. There are also audio compact disks which hold music, etc. and video compact disks for material such as movies. Each type of compact disk has an associated player. There are a variety of compact disk standards.

 Compact disks are a digital storage media, unlike conventional videotape. Therefore
15 copies of such digital material contain all of the information of the original and are a frequent target for pirates (copyright infringers) who make unauthorized copies or otherwise misuse same. There have been developed a number of security systems to prevent unauthorized
~~copying in the compact disk field.~~

 The present invention is directed to a particular aspect of the security problem of
20 compact disks including video CDs and CDRoms (data CDs). Specifically, there is a need for a compact disk player that only plays proprietary CDs, does not play standard CDs, where the proprietary CDs cannot be copied and the proprietary CDs do not play on standard CD players. Thus this is a "closed" system involving proprietary (in terms of the format) CDs and

associated players. A typical application is for a toy system where there is no need to play generally available CDs but only the toy system's CDs are of interest.

Any such system must be relatively inexpensive to implement (since these are consumer players), and must be robust so as to prevent copying, and not interfere with playing
5 and enjoyment of the CD program material. The cost requirement is especially restrictive since even a few dollars of added cost are problematic in consumer electronics. Therefore, well-known methods such as encryption may be problematic since they may require inclusion in the player of a dedicated decryption integrated circuit. Since the decryption must be performed in real time, software decryption is generally less useful in this context.

10

SUMMARY OF THE INVENTION

In an otherwise conventional compact disk player and compact disk, an improvement accomplishes the above goals. This improvement has the above effects of, for the proprietary ("compliant") compact disk player, allowing it only to play compliant CDs; the compliant
15 player will not play standard CDs; the proprietary CDs cannot be copied (that is, if copied they cannot be successfully played on either a compliant player or a standard player); and the compliant CDs do not play on a standard CD player. Thus this creates an entirely closed system in terms of the compliant CDs and associated compliant players. Anyone wishing to play a compliant CD must have a compliant player, the use of which is limited to playing
20 compliant CDs. Of course such a system is targeted to particular markets and requires availability of both the compliant players and the compliant CDs.

In accordance with one aspect of the present invention, a method for recording data on an optical medium is disclosed. In one embodiment, the method includes receiving a first plurality of frames of data at a Cross Interleave Reed-Solomon Code (CIRC) encoder.

encoding the first plurality of frames of data by the CIRC encoder to generate a second plurality of frames of data, generating a set of data to form a Q sub-channel, altering selected data bits in the Q sub-channel to form an encoded Q sub-channel, forming a plurality of control bytes including the encoded Q sub-channel, adding one of the control bytes to each one
5 of the second plurality of frames of data to generate a third plurality of frames of data, encoding selected portions of the third plurality of frames of data by an EFM encoder to generate a plurality of channel frames, and recording the channel frames on the optical medium.

In accordance with another aspect of the present invention, a method for receiving,
10 decoding and presenting data is disclosed. In one embodiment, the method includes receiving a plurality of channel frames of data at an EFM decoder, decoding the channel frames using EFM decoding to generate F3 frames, locating Q sub-channel bits in respective control bytes of the F3 frames, selectively inverting the Q sub-channel bits to generate decoded Q sub-channel information, and decoding and presenting the F3 frames using the decoded Q sub-
15 channel information.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and for further features and advantages, reference is now made to the following description taken in conjunction with the accompanying drawings, in which:

5 FIG. 1A shows a first portion of a process for creating a compliant CD in accordance with this invention:

FIG. 1B shows a continuation of the process of FIG. 1A; and

FIG. 2 is a simplified block diagram of an exemplary CD playback system designed to operate in accordance with the present invention.

10

DETAILED DESCRIPTION OF THE INVENTION

The preferred embodiments of the present invention and their advantages are best understood by referring to FIGURES 1A and 1B of the drawings. Like numerals are used for like and corresponding parts of the various drawings.

15 This invention is generally directed to compact disks and players. It is not limited to CDROMs (typically used for computer data), or video CDs. The embodiment described herein is for video CDs but is applicable to other types of CDs with suitable modifications, as apparent to one skilled in the art from this disclosure.

20 The process described herein is in the context of CDROMs and the terminology is in accordance with the ISO/IEC 10149, Second Edition (1995-07-15) specification for CDROMs, which is incorporated herein by reference in its entirety. With suitable modifications this is applicable to video CDs.

FIGs. 1A and 1B together show a process flow for creating a compliant CD in accordance with this invention. Most of FIGs. 1A and 1B is conventional, except for two data

alterations. Hence while the following description is of the entire CD creation (writing) process, it is to be understood that most of this is conventional and disclosed here only for background purposes. The above specification gives further detail of the data structures on a typical CD. Again this is merely illustrative of one CD specification standard.

5 Beginning in the upper left hand portion of FIG. 1A there is the incoming "sector" data 12. The term "sector" refers to this being digital data already partitioned into sectors.

 This incoming data 12 is in various fields. The associated overhead sync field 14, header field 16, and EDC (Error Detection Code) field 22 are created by the CDRom encoder. The incoming data is put in the user data field 18. The small numerals under each field name
10 designate the field length in bytes. The user data is the largest field. The other fields are the overhead fields.

 The sync field 14 is then passed directly to the next step 14'. This is combined with the IF (intermediate field) field 28. The resulting fields including the IF field 28' are shown below the Reed Solomon processing 32. The IF field is eight bytes of zero value. Added at
15 this point, due to the Reed Solomon processing, is the Q field. The P and Q fields are the Forward Error Correction codes. At this point the header, user data, EDC, P and Q fields are subject to a scrambler 46 using the scrambling algorithm 46. This results in a 2,352 byte data structure 48.

 Processing continues at B. (Reference character B merely shows the continuation of
20 the process.) In FIG. 1B, next is the F1 mapper 52, which maps the 2,352 byte data structure ~~48 into~~ **98 F1 frames designated 0 through 97.** (These frames are not the same as ordinary video frames.) Each F1 frame 54 has a length of 24 bytes.

 Up to this point, all processing is conventional. At this point, scrambling (inversion) in accordance with this invention is introduced by processing the F1 frame data 54 through

inverter 58. (An alternative to this scrambling is encryption.) Inverter 58 accepts one F1 frame at a time, as shown by the switching process 60 which conventionally interleaves the frames. Each frame is subject to a simple bit-by-bit inversion of all its data including the sector address information. Thus each 1 bit is inverted to 0 and each 0 bit is inverted to 1.

5 Subsequent processing is conventional, including the Cross Interleaved Reed-Solomon Code (CIRC) encoding 62. The CIRC encoder as shown accepts data from the inverter or from an audio input.

 The CIRC encoder 62 adds 8 bytes of data to each of the 98 F1 frames. This data is spread out over 106 F2 frames, each of 32 bytes. The F2 frame data which includes the CIRC
10 information from the CIRC encoder 62 thus becomes 106 32-byte frames stored in register 68. This is read out by switching process 70 to become 98 33-byte F3 frames 74, which form a section. F3 frames are identical to F2 frames except for the added control byte 82.

 The information for each frame in the P, Q, R, S, T, U, V and W sub-channels is added as shown to form the control byte 82 of 8 bits. Thus there is a single bit in byte 82 for each
15 sub-channel P through W. These sub-channels are for control purposes. The typical use of the P sub-channel is for an audio player to indicate when the audio starts and stops. The Q sub-channel typically includes the table of contents of the program information in the lead-in area of the disk, and includes index and elapsed time information in the user data area of the disk, as specified in ISO/IEC 10149. The other sub-channels typically are not used.

20 In accordance with this invention, there is an additional scrambling step in which at least the sector address information in the Q sub-channel table of contents is scrambled or otherwise altered by a Q sub-channel encoder 80. Two examples of such alteration of the Q sub-channel are described herein. However, it will be understood that other methods of encoding the Q sub-channel may be used.

In the first example, the entire Q sub-channel, or selected portions thereof, are subject to an inversion. P, Q, R, S, T, U, V, W sub-channel processing is typically performed off-line and, in accordance with this invention, also involves subjecting, in the Q sub-channel, at least the sector address information to an inversion by Q sub-channel encoder 80. Thus at least the
5 sector address information in the Q sub-channel is subject to this inversion, on a bit-by-bit basis. The resulting control byte 82 is then appended to each of the F3 frames.

In the second example of Q sub-channel encoding, a portion of the Q sub-channel is scrambled using an exclusive-OR function in Q sub-channel encoder 80. The Q sub-channel of a 98-frame section typically comprises 96 bits, since the first two control bytes of a section
10 are occupied by the S0 and S1 bytes. The Q sub-channel of a section typically comprises a control field (four bits), a q-Mode field (four bits), a q-Data field (72 bits) and a cyclical redundancy check (CRC) field (16 bits). In accordance with the present invention, the first 80 bits of the Q sub-channel may be scrambled using the XOR function described below, while the last 16 bits which make up the CRC field are computed in the usual fashion.

15 The first 80 bits of the Q sub-channel may be treated as 10 eight-bit bytes. These 10 bytes may be XORed on a byte-by-byte basis with 10 eight-bit encoding bytes. The encoding bytes may be selected arbitrarily. An exemplary set of 10 encoding bytes is set forth in Table

A.

TABLE A

	Byte	Value
	0	01110001
	1	10001110
5	2	00110011
	3	11001100
	4	10101010
	5	01010101
	6	11110000
10	7	00001111
	8	11111111
	9	00000000

15 It will be understood that this second exemplary method of encoding the Q sub-channel simply provides selective inversion of Q sub-channel bits. Wherever a "one" occurs in an encoding byte, the corresponding bit of the Q sub-channel is inverted, while a "zero" in the encoding byte means that the corresponding bit of the Q sub-channel is left unchanged. This is in contrast to the first exemplary encoding method described above, in which all bits of at least
20 a portion of the Q sub-channel are inverted.

This Q sub-channel scrambling, by itself novel and useful, may eliminate the need for the other inverter (inverter 58 in Fig. 1B). Scrambling the Q sub-channel address information may provide some protection, but scrambling most of the information provides more protection. As previously described, the format for the data stored in the Q sub-channel varies
25 depending upon its location on the CD. The general format is data followed by the CRC. In accordance with this invention, the data portion is altered prior to the calculation of the CRC. There is one portion of this data which in some instances may not be altered.

The 98 F3 frames are eventually written to the CD as a series of channel frames, where the first channel frame has the control byte forced to be the conventional S0 sync symbol and

the
SO at

envisio

series of

5 98 F3 frame

looking for eit

systems that use

inverted) SO or SI

standard IC with

10 wrong.

In systems that

inverted so that the SO at

that have them) and that the

The following proce-

15 This requires encoding such t

of ten 0's. This EFM encoding

additionally the merging bits 88

bits (for the sync header) 92 are ac

to the non-return to zero inverted (N

20 written onto a master disk 100. T

"stampers" which press out the plastic

Hence FIGs. 1A and 1B show t

similar process is used except that there i

fields.

SVS2

104.

conversion

5 by CD reading

A conversion

the channel frame

system 106 discard.

A control block

10 frames. The Q sub-channel

110, which performs a de

by Q sub-channel encoder

encoder 80 performs an XOR

sub-channel decoder 110 may

15 the encoded Q sub-channel using

Q sub-channel information. The re-

parts of playback system 102 (not shown)

and presentation of the data from CD 1

The F2 frames generated by conversion

20 which operates in a conventional manner to

or F1 frames. The resulting F1 frames may

(shown in FIGURE 1B) is used in the CD recording

An F1 mapper 116 receives the inverted

function to obtain scrambled sector data, which

CLAIMS

I claim:

1. A method for receiving, decoding and presenting data, comprising:

receiving a plurality of channel frames of data at an EFM decoder:

5 decoding the channel frames using EFM decoding to generate F3 frames:

locating Q sub-channel bits in respective control bytes of the F3 frames:

selectively inverting the Q sub-channel bits to generate decoded Q sub-channel

information: and

decoding and presenting the F3 frames using the decoded Q sub-channel information.

10 2. The method of claim 1, wherein decoding and presenting the F3 frames

comprises:

removing a control byte from each F3 frame to generate an F2 frame;

receiving the F2 frame at a Cross Interleave Reed-Solomon Code (CIRC) decoder; and

15 decoding the F2 frame by the CIRC decoder.

~~3. The method of claim 2, wherein decoding and presenting the F3 frames further~~

~~comprises:~~

~~descrambling the output of the CIRC decoder to generate a data stream; and~~

20 ~~presenting the data stream in a perceptible form to a user.~~

4. The method of claim 3, wherein decoding and presenting the F3 frames further
comprises inverting the output of the CIRC decoder prior to descrambling the output of the
CIRC decoder.

disk:

5

an

a Q

bytes of the F

sub-channel info

a signal

10

operable to decode

information, and oper

6. The optic

presentation system comp

15

a control block oper

frame:

a Cross Interleave Re

decode the F2 frame.

20

7. The optical disk pi

presentation system further compris

a descrambling system opera

generate a data stream: and

5. An optical disk playback system comprising:
- a data reading system operable to read a plurality of channel frames from an optical disk;
 - 5 an EFM decoder operable to decode the channel frames to generate F3 frames;
 - a Q sub-channel decoder operable to locate Q sub-channel bits in respective control bytes of the F3 frames and to selectively invert the Q sub-channel bits to generate decoded Q sub-channel information; and
 - a signal decoding and presentation system operable to receive the F3 frames, and
 - 10 operable to decode the F3 frames to generate a data stream using the decoded Q sub-channel information, and operable to present the data stream in a perceptible form to a user.

6. The optical disk playback system of claim 5, wherein the signal decoding and presentation system comprises:
- 15 a control block operable to remove a control byte from each F3 frame to generate an F2 frame;

~~a Cross-Interleave-Reed-Solomon-Code (CIRC) decoder operable to receiving and~~
decode the F2 frame.

- 20 7. The optical disk playback system of claim 6, wherein the signal decoding and presentation system further comprises:
- a descrambling system operable to descramble the output of the CIRC decoder to generate a data stream; and

a presentation system operable to present the data stream in a perceptible form to a user.

8. The optical disk playback system of claim 7, wherein the signal decoding and presentation system further comprises an inverter operable to invert the output of the CIRC decoder prior to the descrambling of the output of the CIRC decoder by the descrambling system.

9. A method for recording data on an optical medium, comprising:

10 receiving a first plurality of frames of data at a Cross Interleave Reed-Solomon Code (CIRC) encoder;

encoding the first plurality of frames of data by the CIRC encoder to generate a second plurality of frames of data;

generating a set of data to form a Q sub-channel;

15 altering selected data bits in the Q sub-channel to form an encoded Q sub-channel;

forming a plurality of control bytes including the encoded Q sub-channel;

~~adding one of the control bytes to each one of the second plurality of frames of data to~~

generate a third plurality of frames of data;

encoding selected portions of the third plurality of frames of data by an EFM encoder

20 to generate a plurality of channel frames; and

recording the channel frames on the optical medium.

10. The method of claim 9, wherein altering the selected data bits in the Q sub-channel to form the encoded Q sub-channel comprises:

Referring to FIGURE 2, a simplified block diagram of an example of a CD playback system 102 is shown. Playback system 102 includes a CD reading and NRZI decoding system 104, which may include laser optical elements for reading information from CD 100 and a conventional NRZI decoder to extract data bits from the resulting signal. The data generated by CD reading and NRZI decoding system 104 includes data in the form of channel frames.

A conventional EFM decoding system 106 converts the fourteen-Channel bit bytes of the channel frames to eight-bit bytes, thereby generating a series of F3 frames. EFM decoding system 106 discards the merging bits and sync header information from the data stream.

A control block 108 extracts the control bytes from the F3 frames to generate F2 frames. The Q sub-channel data from the control bytes is provided to a Q sub-channel decoder 110, which performs a decoding function corresponding to the encoding function performed by Q sub-channel encoder 80 shown in FIGURE 1B. For example, when Q sub-channel encoder 80 performs an XOR function using a set of encoding bytes as previously described, Q sub-channel decoder 110 may decode the Q sub-channel by performing an XOR function on the encoded Q sub-channel using the same set of encoding bytes, thereby restoring the original Q sub-channel information. The restored or decoded Q sub-channel may then be used by other parts of playback system 102 (not shown) in a conventional manner to assist in the decoding and presentation of the data from CD 100.

The F2 frames generated by control block 108 are provided to a CIRC decoder 112, which operates in a conventional manner to decode the F2 frames to generate either audio data or F1 frames. The resulting F1 frames may be inverted by an inverter 114 if an inverter 58 (shown in FIGURE 1B) is used in the CD recording process.

An F1 mapper 116 receives the inverted F1 frames and uses a conventional mapping function to obtain scrambled sector data, which is then descrambled by descrambler 118 to

restore the original sector data. This sector data is then provided to a presentation system 120, which may include digital to analog converters, speakers, a display screen, or other conventional equipment to present the sector data from CD 100 to a user. Audio data decoded by CIRC decoder 112 may be provided directly to presentation system 120 for presentation to
5 the user.

By performing the inverse of the data encoding functions illustrated in FIGURES 1A and 1B, CD playback system 102 is able to play back a CD 100 recorded using the methods described above, which may not be played back by conventional CD playback systems.

It will be appreciated that the present method and apparatus are not limited to video;
10 also computer data and audio program material on CDs may be protected as disclosed herein. In addition to the above-described scrambling, one may use encryption or other ways of altering, in a systematic or reversible way, the Q sub-channel information.

Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions, and alterations can be made therein
15 without departing from the spirit and scope of the invention as defined by the appended claims.

the second channel frame has the control byte forced to be the conventional S1 sync symbol. S0 and S1 sync symbols have no relationship to the "Sync Header" block 90 in Fig. 1B. If one envisions how an optical pickup head would sense data on a CD, one imagines it as seeing a series of bits being picked up from the disk (i.e., in serial fashion), in order to reconstruct the 98 F3 frames. One needs some way of identifying frame F3-0 or F3-1. This is done by looking for either the S0 or S1 symbols. Therefore one cannot alter the S0 or S1 symbols in systems that use a standard IC (integrated circuit) that only detects the standard (i.e., non-inverted) S0 or S1 symbol. Further, the CRC is not altered either because in systems that use a standard IC with CRC, the verification circuitry would (falsely) determine that the CRC is wrong.

In systems that use standard ICs one must be careful about which parts of the data are inverted so that the S0 and S1 symbols can be successfully detected (in those channel frames that have them) and that the CRC can be recovered correctly.

The following processing in Fig. 1B is conventional, and includes EFM encoding 86. This requires encoding such that between two 1's there a minimum of two 0's or a maximum of ten 0's. This EFM encoding is performed for signal processing purposes. At this point, additionally the merging bits 88 (three per EFM symbol), the sync header 90 and the merging bits (for the sync header) 92 are added, resulting in the channel frame 96. This is then subject to the non-return to zero inverted (NRZI) encoding 98. The NRZI encoded information is then written onto a master disk 100. This master disk is then used conventionally to produce "stampers" which press out the plastic disks which are commercially distributed.

Hence FIGs. 1A and 1B show the CD encoding (writing) process. For video CDs, a similar process is used except that there is no IF field, Reed Solomon processing, or P and Q fields.

The compliant player which is to read the resulting CDs, while largely conventional, includes two suitable logic functions respectively complementary to inverter 58 and Q sub-channel encoder 80. These two functional blocks in the player respectively (1) re-invert data in the data stream and (2) decode the Q sub-channel in accordance with the encoding method
5 used. Hence the compliant player is conventional except for these two additional logic functions. The inverters need not be hardware devices but may be software functions, given adequate processing speed. The same of course is true for the inverter 58 and Q sub-channel encoder 80 in FIG. 1B: they may be hardware logic or software logic functions.

In another embodiment, there may be only one inversion process e.g., in the Q sub-
10 channel or in the data stream rather than two as shown in FIG. 1B. However, it is preferred to have two inversions or alterations as shown in FIG. 1B. This ensures that standard players are unable to play a compliant CD-ROM. In the absence of one of the inversion processes, some conventional (non-compliant) players may be able to play such a compliant disk, which is considered undesirable.

Also, in another embodiment there is no inversion but instead the only change is in the
15 sector address information in the Q sub-channel. In this embodiment, rather than being in the Q sub-channel, the sector address information is instead put in one of the unused sub-channels such as R, S, T, etc. In this case there is no inversion or scrambling. Again the compliant player must be complementary to read the sector address from the correct sub-channel in
20 which this information is now located.

The simple inversion scrambling of FIG. 1B is of course not limiting. Other types of more sophisticated scrambling and/or encryption may be used. However even the simplest type of scrambling is effective in this context.

reading a plurality of stored encoding bits; and

performing an exclusive-OR operation between the selected data bits in the Q-sub-channel and corresponding ones of the encoding bits.

5 11. The method of claim 10, further comprising:

scrambling a sector of data to generate a scrambled sector; and

rearranging the scrambled sector to generate the first plurality of frames of data.

12. The method of claim 11, further comprising inverting the first plurality of
10 frames of data prior to receiving the first plurality of frames of data at the CIRC encoder.

13. The method of claim 9, wherein altering the selected data bits in the Q sub-channel to form the encoded Q sub-channel comprises relocating the selected data bits in the Q sub-channel to respective alternative sub-channel locations of the control bytes.

15

14. An optical disk playback system comprising:

a data reading system operable to read a plurality of channel frames from an optical
disk;

an EFM decoder operable to decode the channel frames to generate F3 frames;

20 a Q sub-channel decoder operable to locate Q sub-channel bits in alternative sub-channel locations in control bytes of the F3 frames to generate Q sub-channel information; and

a signal decoding and presentation system operable to receive the F3 frames, and operable to decode the F3 frames to generate a data stream using the Q sub-channel information, and operable to present the data stream in a perceptible form to a user.

15. A method for recording data on an optical medium, comprising:
- receiving the data at an encoding system
- assigning the data to a plurality of data sets by the encoding system;
- 5 generating address information for each data set;
- encoding the address information for each data set without otherwise altering the data set;
- joining each data set with its respective encoded address information to form an addressed data set;
- 10 recording the addressed data sets on the optical medium.

16. The method of claim 15, further comprising encoding each addressed data set prior to recording the addressed data set on the optical medium.

- 15 17. The method of claim 16, wherein encoding each addressed data set comprises performing EFM encoding on the data set.

18. The method of claim 17, wherein encoding each addressed data set further comprises performing NRZI encoding on the data set.

20

19. ~~The method of claim 15~~, wherein the address information comprises a Q sub-channel.



$\frac{1}{3}$ 

FIG. 1A

2/3



3/3




FIG. 2

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 00/12810

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G11B20/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 10, 31 October 1996 (1996-10-31) & JP 08 153331 A (APPLICS:KK), 11 June 1996 (1996-06-11)	14, 15
A	abstract	1-12
A	WO 98 52114 A (IMATION CORP) 19 November 1998 (1998-11-19) page 7, line 15 -page 10, line 23	1-12
A	EP 0 418 964 A (PHILIPS NV) 27 March 1991 (1991-03-27) column 4, line 34 -column 6, line 4; figures 1-4	1-12
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"Z" document member of the same patent family

Date of the actual completion of the international search

16 October 2000

Date of mailing of the international search report

23/10/2000

Name and mailing address of the ISA

European Patent Office P.O. Box 1218 Patentlaan 2
NL - 1220 HV Rijswijk
Tel: (+31-70) 340-2040, Fax: (+31-70) 340-3016

Authorized officer

Brunet, L

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 00/12810

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>ECMA STANDARDIZING INFORMATION AND COMMUNICATION SYSTEMS: "Standard ECMA - 130 : Data interchange on read-only 120 mm optical disks (CD-ROM)"</p> <p>STANDARD ECMA-130.</p> <p>XP002143627</p> <p>Geneva, Switzerland</p> <p>paragraph '014.! - paragraph '19.1!</p> <p>paragraph '22.0! - paragraph '22.3.6!</p> <p>---</p>	1-19
A	<p>WO 98 03973 A (PHILIPS ELECTRONICS NV ;PHILIPS NORDEN AB (SE))</p> <p>29 January 1998 (1998-01-29)</p> <p>claims 1,2: figures 1-3,7</p> <p>---</p>	14-19
A	<p>WO 98 52194 A (IMATION CORP)</p> <p>19 November 1998 (1998-11-19)</p> <p>page 6, line 14 -page 8, line 2; claim 1</p> <p>---</p>	14-18
A	<p>EP 0 783 167 A (SONY CORP)</p> <p>9 July 1997 (1997-07-09)</p> <p>figures 6.7</p> <p>-----</p>	1,5,9, 14,15

INTERNATIONAL SEARCH REPORT

Information on patent family members

Internal Application No

PCT/US 00/12810

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 08153331 A	11-06-1996	NONE	
WO 9852114 A	19-11-1998	AU 7362198 A	08-12-1998
EP 0418964 A	27-03-1991	AT 118288 T	15-02-1995
		AU 657465 B	16-03-1995
		AU 6266690 A	11-04-1991
		BR 9004656 A	10-09-1991
		CA 2025644 A	22-03-1991
		CN 1050457 A,B	03-04-1991
		CZ 9004536 A	14-07-1999
		DE 69016725 D	23-03-1995
		DE 69016725 T	07-09-1995
		DK 418964 T	10-07-1995
		ES 2070267 T	01-06-1995
		HK 75696 A	10-05-1996
		HU 54822 A,B	28-03-1991
		JP 3108162 A	08-05-1991
		KR 231670 B	15-11-1999
		SU 1836721 A	23-08-1993
		US 5428598 A	27-06-1995
		US 5453968 A	26-09-1995
WO 9803973 A	29-01-1998	CA 2232818 A	29-01-1998
		EP 0852053 A	08-07-1998
		JP 11514126 T	30-11-1999
		US 5930209 A	27-07-1999
WO 9852194 A	19-11-1998	AU 7472998 A	08-12-1998
EP 0783167 A	09-07-1997	JP 9161375 A	20-06-1997
		US 5825731 A	20-10-1998

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.